

PRODUCT OVERVIEW

SERVOTOUGH OxyExact 2200

HAZARDOUS AREA



GAS	MEASURES	APPLICATION
OXYGEN	PERCENT	PROCESS CONTROL COMBUSTION

SENSING TECHNOLOGY

PARAMAGNETIC



KEY APPLICATIONS

- Oxidation control reactions
- Ethylene Oxide (EO), Pure Terephthalic Acid (PTA), and Ethylene Dichloride (EDC) manufacturing
- Catalyst regeneration
- Solvent recovery

HIGH-SPEC PROCESS O₂ ANALYZER OFFERS SAFE OR HAZARDOUS AREA CONTROL WITH UP TO SIX TRANSMITTERS

UNRIVALLED PERFORMANCE

- Uses industry-leading patented Paramagnetic technology for stable, non-depleting measurement
- Manufactured by Servomex - over 60 years' experience innovating and pioneering gas analysis, and thousands of units used in the field every year

FLEXIBLE

- Can be used in hazardous area rated locations including Zone 1 and Division 1
- Samples flammable gas mixtures up to 100% O₂
- High pressure variant allows the handling of samples at 45psia (max) (limited to 21% O₂ above 18psia)
- High temperature variant allows the handling of high dew point samples
- Digital communication options: Ethernet and RS485 Modbus

BENCHMARK COMPLIANCE

- ATEX, IECEx, CSA and FM for Zone 1 and Division 1 monitoring

EASY TO USE

- Six transmitters can be linked to a single control unit, allowing easy device interaction and set-up
- Control unit enclosure allows integration of multiple option cards (4 configurable)
- Internal pressure compensation option to monitor vent pressure variations coupled with high sample pressure option for flare stack applications
- Internal flow alarm option

LOW COST OF OWNERSHIP

- No need for reference/purge gases during measurement in flammable samples
- Simplified transmitter interaction via intuitive control unit (hazardous area or safe area model variants)
- Rugged, resilient design helps ensure long operational life in harsh conditions
- Auto-validation and calibration

For more information please contact us

Visit servomex.com/contact



SERVOMEX.COM

SERVOMEX
a spectris company

PRODUCT OVERVIEW

SERVOTOUGH OxyExact 2200

HAZARDOUS AREA

UNRIVALLED PERFORMANCE FOR THE MOST DEMANDING O₂ PROCESS MONITORING

When you work in hazardous area process monitoring applications, a highly accurate, safe O₂ analytical solution that samples any flammable gas mixture up to 100% O₂ is crucial. No matter what your monitoring requirement, you need an analytical solution that offers operational flexibility, exceptional safety and the opportunity to reduce costs. We don't believe you should have to compromise.

A NO COMPROMISE SOLUTION

The OxyExact's sophisticated, flexible design ethos ensures it can be precisely configured to a wide range of application environments. A single intuitive use controller can be situated in either a safe area or hazardous area, linking to up to six transmitters, permitting simplified set-up and ongoing maintenance through auto-validation and calibration procedures (direct interaction can be facilitated by optional software).

The OxyExact also features a three enclosure design that allows the flexibility to measure flammable gases for 0-100% O₂, helping to reduce costs by removing the need for purge gases.

FLEXIBLE PERFORMANCE YOU CAN DEPEND ON

The OxyExact uses patented Paramagnetic sensing technologies to deliver highly stable and accurate O₂ measurements. Safety-enhanced design and optional flow alarm and pressure compensation ensures sampling versatility - including flare stack applications - that is demanded by your application needs. In addition, Ethernet or RS485 Modbus protocols deliver enhanced communications capabilities. All these aspects combine to make the OxyExact an industry leading solution for O₂ analysis.

USEFUL LINKS



These analyzers are not intended for any form of use on humans and are not medical devices as described in the Medical Devices Directive 93/42/EEC.

Please note: Whilst every effort has been made to ensure accuracy, no responsibility can be accepted for errors and omissions. Data may change, as well as legislation, and you are strongly advised to obtain copies of the most recently issued regulations, standards and guidelines. This document is not intended to form the basis of a contract.

Servomex has a policy of constant product improvement and reserves the right to change specifications without notice. © Servomex Group Limited. 2020. A Spectris company. All rights reserved.

TECHNICAL DATA SHEET

SERVOTOUGH OxyExact 2200 Transmitter



SPECIFICATIONS

TRANSMITTER	2223 (60°C)	2222 (110°C)
GAS MEASURED	OXYGEN (O ₂)	
TECHNOLOGY	Paramagnetic	
PERFORMANCE		
Measurement range	0-100% O ₂ (0-21% O ₂ high pressure variant)	0-100% O ₂
Minimum recommended range	0-0.5%	0-1%
Intrinsic error (accuracy)	<0.02% O ₂	<0.04% O ₂
Zero drift per week	<0.02% O ₂	<0.08% O ₂
Span drift per week	<0.05% O ₂	<0.10% O ₂
Linearity error	<0.01% O ₂	<0.02% O ₂
Repeatability	0.02% O ₂	0.03% O ₂
Response time (T ₉₀)	<4 seconds at 250ml/min (low flow range) <4 seconds at 1l/min (high flow range)	
Output noise (within any 5 minute period)	<0.01% O ₂ peak to peak	<0.02% O ₂ peak to peak
Effect of ambient temperature changes	Zero change per 10°C (18°F) ambient change ± 0.02% max Span change per 10°C (18°F) ambient change ± 0.2% max	
Sample flow variations	A change in flow from 50-250ml/min (0.2-1.2l/min internal bypass option) will cause a change of 0.1% O ₂ max	
Effect of barometric pressure or sample vent pressure	Pressure compensation not fitted: 1% change in pressure corresponds to a 1% change in reading Pressure compensation fitted: 1% change in pressure corresponds to a ±0.02% O ₂ change*	Pressure compensation not fitted: 1% change in pressure corresponds to a 1% change in reading
Effect of supply voltage variation of ±10%	<0.01% O ₂ or 0.1% of reading, whichever is the greater	0.02% O ₂ or 0.2% of reading whichever is the greater
Effect of supply interruptions	A single cycle interruption in electrical supply will have no effect on the analyzer	
Altitude sensitivity	Less than 0.01% O ₂ per degree of tilt from altitude at time of calibration	
Zero suppression	The Zero may be suppressed in 0.01% steps to a maximum of 99.99% suppression	
SIGNAL OUTPUTS/INPUTS		
Analog output	Single 'intrinsically safe' 0/4-20mA. Maximum impedance 600W. The output can be made to jam high or low under fault conditions	
Alarms & relays	Three intrinsically safe 'volt free' single pole contacts, allocated to NAMUR (fault, maintenance required, in calibration/service mode)	
Analog inputs	Two 'intrinsically safe' 0/4-20mA linear inputs designed for external pressure compensation and background gas cross-interference correction. Two 'intrinsically safe' NAMUR flow sensor inputs	
Digital inputs	Four 'intrinsically safe' inputs, customer assignable, for example, to manual calibration or validation of 4-20 mA inputs	
Control unit connection	Single "i.s." twisted pair	

* Pressure compensation reduces the effect by a factor of 200 or ±0.02% - whichever represents least compensation

The performance specification has been written and verified in accordance with the international standard IEC 61207-1:1994 "Expression of performance of gas analyzers"



SERVOMEX.COM

SERVOMEX 
a spectris company

PHYSICAL		
TRANSMITTER	2223	2222
Ingress protection	IP66, NEMA 4X	
Weight	16kg (35.3lbs)	
Dimensions, WxDxH	432 (W) x 303 (H) x 210mm (D)	
Mounting	Wall mount	

OPERATING ENVIRONMENT		
Temperature	Operation: -20°C to +50°C (-4°F to +122°F) Storage: -20°C to +70°C (-4°F to +158°F)	Operation: -10°C to +50°C (+14°F to +122°F) Storage: -20°C to +70°C (-4°F to +158°F)
Atmospheric pressure	76 to 112kPaa (11 to 16.2psia)	
Warm up time	Useable immediately, but typically 2 hours (from 20°C)	Typically 6 hours (from 20°C)
Relative humidity	0-95% non-condensing	
Max altitude	3,000m (9,842ft)	

SAMPLE CONDITION			
TRANSMITTER	2223 (standard)	2223 (high pressure)	2222
Maximum measurable oxygen concentration	100%	21%	100%
Inlet pressure	Max: 0.3kPa (0.04psig), relative to vent pressure	Max: 0.3kPa (0.04psig), relative to vent pressure	Max: 0.3kPa (0.04psig), relative to vent pressure
Sample pressure (maximum)	28kPag (4psig) standard	<45psia	28kPag (4psig) standard
Inlet flow rate	250ml (air)/minute or 1l/min depending upon version	250ml (air)/minute or 1l/min depending upon version	250ml (air)/minute or 1l/min depending upon version
Dew point	5°C (9°F) below lowest ambient temp	5°C (9°F) below lowest ambient temp	105°C max
Temperature	-10°C to +50°C (+14°F to +122°F)	-10°C to +50°C (+14°F to +122°F)	-10°C to +105°C (+14°F to +221°F)
Particulates	maximum 3µm	maximum 3µm	maximum 3µm
Inlet connection	1/8" NPT Female	1/8" NPT Female	1/8" OD Pipe
Outlet connection	1/8" NPT Female	1/8" NPT Female	1/8" OD Pipe
Condition	Clean, dry, free from oil and condensates	Clean, dry, free from oil and condensates	Clean, dry, free from oil and condensates

UTILITIES	
Supply voltage	100-120V ac, 50/60 Hz or 220-240V ac, 50/60 Hz 2223: 100VA 2222: 100VA



SAMPLE WETTED MATERIALS

TRANSMITTER	2223	2222
Borosilicate glass	•	•
Electroless Nickel	•	•
Platinum	•	•
Platinum/iridium alloy	•	•
316 stainless steel	•	•
Hastelloy	•	•
Viton®	•	•
PTFE	•	•
Chemraz®	•	•

COMPLIANCE

HAZARDOUS AREA APPROVALS		
TRANSMITTER	2223	2222
ATEX (Europe)	Ex II 2(I)GD Ex db ia [ia Ga] IIC T4 Gb Ex tb IIIC T70°C Db IP66 (-20°C < Ta < +50°C)	Ex II 2(I)GD Ex db ia [ia Ga] IIC T3 Gb Ex tb IIIC T70°C Db IP66 (-10°C < Ta < +50°C)
FM (USA)	Class I, Division 1, Groups A,B,C and D Class II, Division 1, Groups E, F and G Class III, Division 1 T4, ambient temperature 50°C maximum	Class I, Division 1, Groups A,B,C and D Class II, Division 1, Groups E,F and G Class III, Division 1 T3, ambient temperature 50°C maximum
FM Zones (USA)	Class I, Zone 1 approval, AEx d ia IIC T4 (Ta = 50°C)	Class I, Zone 1 approval, AEx d ia IIC T3 (Ta = 50°C)
CSA (Canada)	Class I, Division 1, Groups A,B,C and D Class II, Division 1, Groups E,F and G Class III Type 4X, T4, ambient temperature 50°C maximum	Class I, Division 1, Groups A,B,C and D Class II, Division 1, Groups E,F and G Class III Type 4X, T3, ambient temperature 50°C maximum
CSA Zones (Canada)	Class I, Zone 1 approval, Ex d ia [ia] IIC T4 (Ta = 50°C)	Class I, Zone 1 approval, Ex d ia [ia] IIC T3 (Ta = 50°C)
IECEx (other)	Ex db ia [ia Ga] IIC T4 Gb Ex tb IIIC T70°C Db IP66 (-20°C ≤ Ta ≤ +50°C)	IEC Ex db ia [ia Ga] IIC T3 Gb Ex tb IIIC T80°C Db IP66 (-10°C ≤ Ta ≤ +50°C)
CML (Japanese)	Ex db ia [ia Ga] IIC T4 Gb Ex tb IIIC T70°C Db IP66 (-20°C ≤ Ta ≤ +50°C)	Not available
EC DIRECTIVES	2223 & 2222 Transmitters comply with the EMC Directive, RoHS II, and all other applicable directives.	
ELECTRICAL SAFETY	Electrical safety to IEC 61010-1	



TRANSMITTER CONFIGURATION	
Transmitter versions	There are two versions of the OxyExact 2200. The 2223 measurement compartment is controlled at 60°C, whilst the 2222 measurement compartment operates at 110°C. The higher sample compartment temperature of the 2222H results in some options not being available for this transmitter unit.
Transmitter type	5 certified versions of the Oxy analyzer are available for the 2233 transmitter version: European ATEX, International IECEx, North American FM, Canadian CSA and Japanese. Japanese certification is not available for the 2222H. Refer to certification section for full details.
Supply voltage	Two versions of supply voltage are available: 100-120 and 220-240V ac.
User manual	An Installation manual that contains all of the information needed to install and safely set up the analyzer.
Service manual	A Service manual contains technical descriptions, fault diagnosis, parts removal, refitting and test instructions, tool and test equipment lists and electrical drawings. It is intended for use by Servomex trained service personnel. The Service manual covers both the OxyExact 2200 control unit and transmitters.
Electrical entry option	As standard the transmitter unit is supplied with 5 gland entries, 3 x 1/2" NPT female and 2 x 3/4" NPT.
Sample wetted materials	As standard the transmitter sample pipework is stainless steel. Optionally for the 2223 version the internal pipework can be configured to be of Hastelloy construction for improved resistance to acidic or highly corrosive sample gases.
Sample cell type	The standard sample cell contains Viton® o-rings and is suitable for sample pressures up to 28kPag (4psig) and oxygen concentrations up to 100%. The 'High pressure' solvent resistant cell utilises Chemraz® o-rings and is suitable for sample gas pressures up to 45psia with non-enriched oxygen samples (<21%). The 2222H is only supplied with the High Pressure Solvent Resistant cell option.
Sample flow	Standard flow option of 250ml/min.
An internal bypass option allows sample gas inlet flows of up to 1l/min.	The sensor head is supplied with an equivalent PCD 4" ANSI 150lbs flange as standard. Adaptors are available to suit other flange sizes. The analyzer is not designed to withstand 150lbs pressure. The flue pressure should be a maximum of 5psig.
Internal sample filter	Option to fit an internal 20micron filter within the sample gas inlet port to add additional protection to fine dust particles entering the precision paramagnetic cell. Use of the internal filter is always recommended. The inlet filter is not designed to be the primary protection of particulates in any associated sample system.
Flow alarm	The measurement of the analyzer is highly reliable and has internal diagnostics to ensure correct operation, yet in low flow conditions the measurement accuracy may be affected and this cannot be diagnosed by the instrument without a flow sensor. Our Flowcube technology offers an internal solid state flow sensor fitted directly to the outlet of the measurement transducer, ensuring that the measurement gas is flowing through the transducer at all times for maximum reliability and safety. <i>(Note: the flow sensor is currently not suitable for gas mixtures that differ significantly in thermal conductivity from that of Nitrogen. Sample gases containing hydrogen and/or helium at concentrations over 10% of the total mixture are no suitable).</i>
Pressure compensation	The uncorrected gas measurement is directly affected by changes in atmospheric pressure and any sample vent back pressures on the sample outlet. A 1% change in pressure will directly affect the measurement by 1% of reading. This needs to be considered when looking at the measurement performance required. The fitting of the internal pressure transducer reduces the effect of pressure changes by a factor of 50. A 1% change in pressure will result in a less than 0.02% change in sample reading. Internal pressure compensation is not available as an option in the 2222H transmitter. Instead, if sample pressure compensation is required, a 4-20mA input is available for connection to a customer supplied sample pressure signal (i.s barrier required) and external compensation parameters can be configured via the control unit menu system.
Sample inlet adaptors	Allows the connection of 1/8" NPT male fittings directly to the analyzer as standard. Optionally, for the 2223 version only, adaptors can be configured to adapt the sample entries to:- 1/4" OD tube directly to the analyzer 6mm OD tube directly to the analyzer
Corrosive sample purge	A 1/8" NPT female inlet & outlet fitting allows inert gas to be supplied to the analyzer to prevent the build-up of any corrosive gases within the sample compartment. Purge gas should be clean dry air or an inert gas controlled to a flowrate no higher than 50ml/min. This will extend the operational life of the analyzer in such environments.
Functional safety / SIL manual	International instructions for those planning, designing, installing, commissioning and maintaining Safety Instrumented Systems. Demonstrates analyzer hardware compliance to IEC 61508.



CONFIGURATION	SERVOTOUGH OxyExact Transmitter 2223	
Transmitter type	Hazardous Area ATEX Cat 2 (Zone 1)	☐
	Hazardous Area FM Div 1	☐
	Hazardous Area CSA Div 1	☐
	IEC Ex	☐
	CML Ex	☐
Supply voltage	100-120V 50/60Hz	☐
	220-240V 50/60Hz	☐
User manual	Not required	☐
	English	☐
Service manual	English	☐
Electrical entry option	3/4" NPT	☐
	M20 adaptor kit	☐
	PG13.5 adaptor kit	☐
Sample wetted material	Stainless steel	☐
	Hastelloy	☐
Sample cell type	Standard	☐
	High pressure solvent resistant	☐
Sample flow	250ml/min	☐
	1l/min	☐
Internal sample filter	Fitted	☐
	Not required	☐
Flow alarm	Fitted, internal	☐
Pressure compensation	Fitted, internal	☐
Sample inlet adaptors	Standard (1/8" NPT (F))	☐
	1/4" OD adaptor	☐
	6mm OD adaptor	☐
Corrosive sample purge	Fitted	☐
Functional safety/SIL manual	Not required	☐
	English	☐




CONFIGURATION	SERVOTOUGH OxyExact Transmitter 2222 (High Temperature)	
Transmitter type	Hazardous Area ATEX Cat 2 (Zone 1) ☐ Hazardous Area FM Div 1 ☐ Hazardous Area CSA Div 1 ☐ IEC Ex ☐	
Sample temperature	110°C set point (T3 rating) ☐	
Supply voltage	100-120V 50/60Hz ☐ 220-240V 50/60Hz ☐	
User manual	Not required ☐ English ☐	
Service manual	English ☐	
Electrical entry option	3/4" NPT ☐ M20 adaptor kit ☐ PG13.5 adaptor kit ☐	
Sample wetted material	Stainless steel ☐	
Sample cell type	High pressure solvent resistant ☐	
Sample flow	250ml/min ☐ 1l/min ☐	
Internal sample filter	Fitted ☐ Not required ☐	
Flow alarm	Fitted ☐	
Sample inlet adaptors	1/8" OD tubes ☐	
Corrosive sample purge	Fitted ☐	
Functional safety/SIL manual	Not required ☐ English ☐	



DIMENSIONAL DRAWINGS


TRANSMITTER UNIT

ATEX Category 2 (02222H)



1. Sample gas connections
2. Power cable entry
3. Functional (EMC) earth/ground terminal
4. Signal cable entry
5. Signal cable entry
6. Signal cable entry
7. Signal cable entry
8. Corrosive purge gas outlet
9. Corrosive purge gas inlet

ATEX Category 2 (02223)



1. Sample gas connections
2. Power cable entry
3. Functional (EMC) earth/ground terminal
4. Signal cable entry
5. Signal cable entry
6. Signal cable entry
7. Signal cable entry
8. Corrosive purge gas outlet
9. Corrosive purge gas inlet

Dimensions shown in millimetres



SERVOMEX.COM



SERVOMEX
ANALYZERS
HIGH-PERFORMANCE GAS ANALYSIS

TECHNICAL DATA SHEET



SERVOTOUGH OxyExact 2200 Control Unit

SPECIFICATIONS

PERFORMANCE	
Display resolution	User configurable with maximum 4 decimal places (0.001%)
Control Unit mA output resolution	Whichever is the greater: 0.001% oxygen or 0.002% of mA output span
DIGITAL COMMUNICATIONS	
Modbus communications protocol	Modbus RTU (RS485) provided as standard or optionally Ethernet Modbus TCP/IP (standard RJ45 connection)
SIGNAL INTERFACE CARDS OPTIONS	
<i>A maximum of four signal interface cards may be installed in any combination</i>	
Milliamp Output Card	Two mA outputs and two 'low power' relays per card Two isolated 0-20mA/4-20mA outputs with full configuration of zero and span. The user may define a second range and invoke it by means of an external output contact closure. Maximum impedance for each output is 1KΩ. All outputs may be configured in 'reverse' and the maximum current for all outputs is 21.5mA. Two 'low power' relays rated 30V ac/dc @ 1Amp, customer assignable to 'NAMUR' status alarms, alarm, auto-calibration or remote range change functions. The mA output can be made to 'Jam' high or low on a fault condition in accordance with NAMUR 43.
Relay Output Card	Four 'high power' relays per card Four 'high power' relays per relay option card rated at 240V ac/30V dc @ 1.0Amp, customer assignable to NAMUR status alarms, measurement alarm, fault or auto-calibration functions.
Digital Input Card	Eight digital inputs per card Eight digital inputs per option card, customer assignable Potential use: • Autocalibration initiation • Remote range change • Validity of mA inputs • Digital flow sensors
FEATURES	
Display	Graphics LCD display with LED backlight and integral keypad (seven button)
User Interface	Software has multi-language menu capability (English, French and German languages) with standard status pane icons User interface is has six user configurable measurement display pages with up to six measurements displayed on each page
Security	Four level user configurable password protection as standard
Transmitter Connection	Up to six transmitters can be connected to a single control unit
Transmitter Separation	Maximum permissible separation between a single transmitter and control unit is 1,000m. Please consult Servomex for the maximum separation between multiple transmitters and a single control unit



SERVOMEX.COM



SERVOMEX
ANALYZERS
HIGH-PERFORMANCE GAS ANALYSIS

OPERATING ENVIRONMENT		
Temperature	Operation: -10 to +50°C (+14°F to +122°F) in sheltered location Storage: -20°C to +70°C (-4°F to +158°F)	
Atmospheric pressure	76 to 112 kPaa (11 to 16.2psia)	
Warm up time	Useable immediately, but typically 2 hours from cold start at 20°C	
Relative humidity	0-95% non-condensing	
Max altitude	3,000m (9,842ft)	
PHYSICAL		
CONTROL UNIT	2210	2213
Ingress protection	IP66, NEMA 4X	
Weight	10kg (22 lbs)	25kg (55.1 lbs)
Dimensions, WxDxH	280 (W) x 300 (H) x 250mm (D)	505 (W) x 325 (H) x 255mm (D)
Mounting	Wall mount	
UTILITIES		
Supply voltage	100-120V ac, 50/60 Hz or 220-240V ac, 50/60 Hz 2210: 30VA 2213: 50VA	

COMPLIANCE

HAZARDOUS AREA APPROVALS		
CONTROL UNIT	2210	2213
ATEX	 II 3(1)GD Ex ic nA nC [ia Ga] IIC T4 Gc  tc IIIC T70°C Dc IP66 (-20°C < Ta < +50°C)	 II 2(I)GD Ex db ia [ia Ga] IIC T4 Gb  tb IIIC T70°C Db IP66 (-20°C < Ta < +50°C)
FM (USA)	Class I, Division 2, Groups A,B,C, and D Class II, Division 2, Groups F and G Class III, Division 2 T4, ambient temperature 50°C maximum	Class I, Division 1, Groups B,C and D Class II, Division 1, Groups E, F and G Class III, Division 1 T4, ambient temperature 50°C maximum
FM Zones (USA)	Class I, Zone 2 approval, IIC T4 (Ta = 50°C) with IS outputs	Class I, Zone 1 approval AEx d ia [ia IIC] IIB + H2 T4 (Ta = 50°C)
CSA (Canada)	Class I, Division 2, Groups A,B,C and D Class II, Division 2, Groups E,F and G Class III Type 4X, T4, ambient temperature 50°C maximum	Class I, Division 1, Groups B,C and D Class II, Division 1, Groups E,F and G Class III Type 4X, T4, ambient temperature 50°C maximum
CSA Zones (Canada)	Ex nA nL nC ia [ia] IIC:T4	Class I, Zone 1 approval, Ex d ia [ia] IIB + H2, T4 (Ta = 50°C)
IECEx (other)	Ex ic nA nC [ia Ga] IIC T4 Gc Ex tc IIIC T70°C Dc IP66 (-20°C ≤ Ta ≤ +50°C)	Ex d ia [ia Ga] IIC T4 Gb Ex tb IIIC T70°C Db IP66 (-20°C ≤ Ta ≤ +50°C)
CML (Japanese)	Not applicable	Ex d ia [ia Ga] IIC T4 Gb Ex tb IIIC T70°C Db IP66 (-20°C ≤ Ta ≤ +50°C)
EC DIRECTIVES	2210 & 2213 Control Units comply with the EMC Directive, RoHS II, and all other applicable directives	
ELECTRICAL SAFETY	Electrical safety to IEC 61010-1	



CONTROL UNIT CONFIGURATION	
Control unit versions	There are two versions of the OxyExact 2200 control unit. The 2210 is a single compartment build and is certified for Zone 2 / Class 1 Div 2 installations whilst the 2213 uses an Exd compartment with separate intrinsically safe section for the screen and keypad to raise the certification to Zone 1 / Class 1 Div 1.
Controller type	4 certified versions of the Oxy analyzer are available for the 2210 controller version: European ATEX, International IECEx, North American FM, and Canadian CSA. Japanese certification is not available for the 2210. Refer to certification section for full details.
Supply voltage	Two versions of supply voltage are available: 100-120 and 220-240V ac.
User manual	An Installation manual that contains all of the information needed to install and safely set up the analyzer.
Service manual	A Service manual contains technical descriptions, fault diagnosis, parts removal, refitting and test instructions, tool and test equipment lists and electrical drawings. It is intended for use by Servomex trained service personnel. The Service manual covers both the OxyExact 2200 control unit and transmitters.
Electrical entry option	As standard the controller unit is supplied with: 2210 controller - 7 gland entries, 2 x ½" NPT female and 5 x ¾" NPT 2213 controller - 8 gland entries, 3 x ½" NPT female and 5 x ¾" NPT Adaptors to M20 gland entries supplied (optional) Adaptors to Pg13.5 gland entries supplied (optional)
Slot module option 1	Four option slots exist that can be configured with any combination of boards from the list below. All outputs and inputs are software configurable via the control unit user interface. • mA output card – two 4-20mA outputs and two low voltage relays with changeover contacts. • Relay output card – four relays with changeover contacts • Digital input card – eight channels
Slot module option 2	
Slot module option 3	
Slot module option 4	
Data communication	This allows for the analyzer to be fully maintained and configured remotely. It also allows for a greater level of remote diagnostics to be carried out above that supplied by the relay contacts. As standard the controller is configured with RS485 Modbus protocol output. Optionally the control unit can be configured with Modbus Ethernet TCP/IP protocol.
Enclosure options	As standard the enclosure is not fitted with a breather vent. Optionally a breather vent can be configured to allow the complete enclosure in the case of the 2210 controller, or the intrinsically safe section, for the 2213 controller.
Controller mounting	The OxyExact 2200 controller is available in a wall mount option only.



CONFIGURATION	SERVOTOUGH OxyExact 2210 Controller	
Controller type	Hazardous Area ATEX Cat 3 (Zone 2) ☐ Hazardous Area FM Div 2 ☐ Hazardous Area CSA Div 2 ☐ IEC Ex ☐	
Supply voltage	100-120V 50/60Hz ☐ 220-240V 50/60Hz ☐	
User manual	English ☐	
Service manual	English ☐	
Electrical entry option	3/4" NPT ☐ M20 adaptor kit ☐ PG13.5 adaptor kit ☐	
Slot 1 module option	mA output board ☐ Relay board ☐ Digital input board ☐	
Slot 2 module option	mA output board ☐ Relay board ☐ Digital input board ☐	
Slot 3 module option	mA output board ☐ Relay board ☐ Digital input board ☐	
Slot 4 module option	mA output board ☐ Relay board ☐ Digital input board ☐	
Data communication	Modbus protocol (RS485) ☐ Modbus protocol Ethernet ☐	
Controller mounting	Wall ☐	




CONFIGURATION	SERVOTOUGH OxyExact 2213 Controller	
Controller type	Hazardous Area ATEX Cat 2 (Zone 1)	☐
	Hazardous Area FM Div 1	☐
	Hazardous Area CSA Div 1	☐
	IEC Ex	☐
	CML Ex	☐
Supply voltage	100-120V 50/60Hz	☐
	220-240V 50/60Hz	☐
User manual	Not required	☐
	English	☐
Service manual	English	☐
Electrical entry option	3/4" NPT	☐
	M20 adaptor kit	☐
	PG13.5 adaptor kit	☐
Slot 1 module option	Not required	☐
	mA output board	☐
	Relay board	☐
	Digital input board	☐
Slot 2 module option	Not required	☐
	mA output board	☐
	Relay board	☐
	Digital input board	☐
Slot 3 module option	Not required	☐
	mA output board	☐
	Relay board	☐
	Digital input board	☐
Slot 4 module option	Not required	☐
	mA output board	☐
	Relay board	☐
	Digital input board	☐
Data communication	Modbus protocol (RS485)	☐
	Modbus protocol Ethernet	☐
Enclosure option	Breather	☐



DIMENSIONAL DRAWINGS


CONTROL UNIT

ATEX Category 3 (02210)



- 1. Surface mount fixing hole
- 2. Display window
- 3. Keypad
- 4. Door, in open position
- 5. Power and signal cable entries
- 6. Functional (EMC) earth/ground terminal
- 7. Transmitter connection cable entries

ATEX Category 2 (02213)



- 1. Surface mount fixing hole
- 2. Display window
- 3. Keypad
- 4. Door, in open position
- 5. Power and signal cable entries
- 6. Functional (EMC) earth/ground terminal
- 7. Transmitter connection cable entries

Dimensions shown in millimetres



> WE'RE READY TO HELP

WHATEVER YOUR GAS ANALYSIS REQUIREMENTS, WHEREVER YOU ARE

These analyzers are not intended for any form of use on humans and are not medical devices as described in the Medical Devices Directive 93/42EEC.

Please note: *Whilst every effort has been made to ensure accuracy, no responsibility can be accepted for errors and omissions.*

Data may change, as well as legislation, and you are strongly advised to obtain copies of the most recently issued regulations, standards and guidelines.

This document is not intended to form the basis of a contract.

Servomex has a policy of constant product improvement and reserves the right to change specifications without notice. © Servomex Group Limited. 2020.
A Spectris company. All rights reserved.