

ZWICK
ARMATUREN GMBH



TRI-CON

**SERIES FOR
DISTRICT HEATING
AND POWER PLANTS**

HIGH STANDARD VALVES FOR NON-STANDARD CONDITIONS.

TRIPLE OFF-SET DESIGN

Frictionless during opening and closing.

METAL SEATED

Multi layer seal ring is statically and reliable held the on disc.

SELF-CENTERING DISC DESIGN

Accommodates certain thermal expansions of valve parts during temperature increase.

Reliable torque transmission through key connection (no pinning).


100% MADE IN GERMANY

Highest demands to valve quality.



GENERAL CHARACTERISTICS

Pressure class: PN 10/16/25/40/63/100
Leakage class: Class A acc. DIN EN 12266-1
bi-directional
Temperature: up to +815°C
Sizes: DN 50-2200
Certificates: TP TC 010 и 032 (EAC)



TRI-CON

Shut-off and control butterfly valves.

TRI-SHARK

Control valves for severe applications (with "SHARK TOOTH" cartridge). Control range up to 100:1 (from 1% KVs). Reduced disc on request.

TRI-CHECK

Check valves.

Valve combination (check valve with control function, assisted opening, assisted closing).

ZWICK
ARMATUREN GMBH

Egerstr. 1 & 25
D-58256 Ennepetal
TEL +49 (0) 23 33 / 98 56 5
FAX +49 (0) 23 33 / 98 56 6
MAIL info@zwick-gmbh.de

WWW.ZWICK-VALVES.COM