

SIL3



TRI-BLOCK

DOUBLE BLOCK AND BLEED

HIGH STANDARD VALVES FOR NON-STANDARD CONDITIONS.

MATERIALS

Standard and special material available:

- Steel: 1.0619, P265GH, 1.6220, WCB, A516Gr.70, etc.
- Stainless Steel: 1.4408, 1.4308, 1.4571, CF8M, CF3, SS316Ti, etc.
- Duplex Steel: 1.4462, 1.4468, 1.4469
- Special Alloys: Monel, Inconel, Hastelloy, HVD-1, 1.4539, 904/904L

OPTIONAL SEALED CONSTRUCTION

- Patented sealed bearing
- No cracking of medium during storage
- Sealed clamp ring design

AVAILABLE CERTIFICATES

- TA Luft II
- ISO 15848
- SIL 2
- API 641
- Fire Safe Design 10497
- SIL 3

- Triple eccentric butterfly valve
- Self centering disc
- DN 50 – 2200 / 2" – 88"
- PN 6 – 160 / ANSI 150 – 1500
- Metal sealing
- Leakage rate A acc. to DIN EN 12266-1 for liquids und gases
- -215°C to +815°C



APPLICATIONS

- C3 / C4 / Butadiene
- Hydrogen
- Oxygen
- NH3
- Hydrocarbons
- Technical Gases
- Syngas
- Water / Steam / Condensate / Vapors
- MDI



ZWICK
ARMATUREN GMBH

Egerstr. 1 & 25
D-58256 Ennepetal
TEL +49 (0) 23 33 / 98 56 5
FAX +49 (0) 23 33 / 98 56 6
MAIL info@zwick-gmbh.de

WWW.ZWICK-ARMATUREN.DE